



Scripting Languages

Laszlo SZATHMARY

University of Debrecen

Faculty of Informatics

Lab #4

- what is evaluated as False; string buffer
- tuple data type
- list comprehension
- control structures
- functions

(last update: 2023-02-06 [yyyy-mm-dd])

2022-2023, 2nd semester





What is evaluated as False?

False
None
0 # and: 0.0
" # or: ""
[]
()
{ }

} empty sequences
} empty set

```
>>> bool(None)  
False  
>>> bool([])  
False  
>>> bool([1,2,3])  
True  
>>> bool("py")  
True
```

Anything else is considered to to be True.

HW: XOR.

<http://docs.python.org/3/library/stdtypes.html#truth-value-testing>



String buffer

Example: consider the natural numbers from 1 to 15 (included) and write them down one after the other. Let the result be a string:

„123456789101112131415”.

String buffer

Example: consider the natural numbers from 1 to 15 (included) and write them down one after the other. Let the result be a string:
„123456789101112131415”.

Naïve approach:

```
5 res = ""
6 for i in range(1, 15+1):
7     res += str(i)
8 #
9 print(res)
```

Using a string buffer:

```
5 parts = []
6 for i in range(1, 15+1):
7     parts.append(str(i))
8 #
9 res = "".join(parts)
10 print(res)
```

tuple

```
4 >>> a = (1, 2, 3)
5 >>> a[0]
6 1
7 >>> a[0] = 5
8 Traceback (most recent call last):
9   File "<stdin>", line 1, in <module>
10  TypeError: 'tuple' object does not support item assignment
11 >>>
12 >>> m = ('Total Recall', 1990, 7.5)
13 >>> m
14 ('Total Recall', 1990, 7.5)
15 >>> len(m)
16 3
17 >>> m[:2]
18 ('Total Recall', 1990)
19 >>>
20 >>> (x, y) = (1, 2)
21 >>> x
22 1
23 >>> y
24 2
25 >>> single = ('hi',)
26 >>> single
27 ('hi',)
```

immutable
(read-only)

parallel assignment
(parentheses are
often optional)

tuple with one element
(Notice the special syntax!)

HW: [tuple02.py](#)

```
4 def get_movie_info():
5     # contact database,
6     # fetch info from a website, etc.
7     return ('Total Recall', 1990, 7.5)
8
9
10 def main():
11     (title, year, score) = get_movie_info()
12     print('Title:', title)
13     print('Year:', year)
14     print('Score:', score)
```

using this method, a function can return **multiple values**


value unpacking

```
1 >>> a = 3
2 >>> b = 9
3 >>> a
4 3
5 >>> b
6 9
7 >>> a, b = b, a
8 >>> a
9 9
10 >>> b
11 3
12 >>>
```

Swap two variables.
No temp variable is needed :)

List comprehension: a compact way for building lists

```
1 >>> nums = [1, 2, 3, 4]
2 >>> squares = [n*n for n in nums]
3 >>> squares
4 [1, 4, 9, 16]
```



```
1 >>> nums = [1, 2, 3, 4]
2 >>> squares = []
3 >>> for n in nums:
4 ...     squares.append(n*n)
5 ...
6 >>> squares
7 [1, 4, 9, 16]
```

Generally:

```
[expr for var in list]
```

Optional „if“:

```
1 >>> nums = [8, 3, 2, 1, 5, 9, 2]
2 >>> small = [n for n in nums if n <= 2]
3 >>> small
4 [2, 1, 2]
5 >>>
```

it keeps only those elements
that satisfy the condition



Exercise

Solve the following exercises with list comprehensions.

Link: <https://arato.inf.unideb.hu/szathmary.laszlo/pmwiki/index.php?n=EnPy3.20120818d>

Common operation: reverse a sequence

```
1 >>> s = 'Python rulz'
2 >>> s[::-1]
3 'zlr nohtyP'
4 >>>
5 >>> li = [23, 76, 84, 12]
6 >>> li[::-1]
7 [12, 84, 76, 23]
8 >>>
```

from the beginning to the end,
but with a reversed step
(it returns a new sequence)

Raising to a power; int and long types

```
1 >>> 2**3
2 8
3 >>> 2**64
4 18446744073709551616L
5 >>> 2**128
6 340282366920938463463374607431768211456L
7 >>>
8 >>> import sys
9 >>> sys.maxint
10 9223372036854775807
11 >>> a = sys.maxint + 1
12 >>> a
13 9223372036854775808L
14 >>> type(sys.maxint)
15 <type 'int'>
16 >>> type(a)
17 <type 'long'>
```



Python can handle arbitrarily
large integers
(only depends on the memory)

here: 64 bit int ($2^{63} - 1$)

instead of an overflow, its type
is changed automatically from
„int” to „long”

Python 3: there is only *int* type, but
in the case of big numbers it behaves
like *long* .

if / elif / else

```
4 def main(num):  
5     if num < 0:  
6         print('Negative number.')7     elif num == 0: ←  
8         print('Zero.')9     elif num < 100:  
10        print('Less than 100.')11    else:  
12        print('More than 100.')
```

>= 100, actually

Instead of „else if” we write „elif”.

How to memorize that? The word „elif” is just as long as the word „else” ...

for

```
4 def main():  
5     li = ['alfa', 'beta', 'gamma']  
6  
7     for e in li:  
8         print(e)  
9  
10    for index, e in enumerate(li):  
11        print(index, e)
```

alfa
beta
gamma

0 alfa
1 beta
2 gamma

It's a common case that we also need the indexes of the elements.

Use the `enumerate()` function, which is also an iterator in Python 3.

See also `enumerate(my_list, start=1)`.

break / continue pass

```
4 def main():
5     cnt = 0
6     while True:
7         cnt += 1
8         if cnt == 42:
9             break
10    #
11    print(cnt)    # 42
12
13    li = ['anas', 'banana', 'orange']
14    for e in li:
15        if e == 'banana':
16            continue
17        #
18        print(e)
19
20
21 def palindrome(s):
22    pass    # TODO...
```

← 42

← ananas
orange

← empty statement



docstring

Documentation should be one line:

```
4 def square(num):  
5     """Return the square of a given number."""  
6     return num ** 2
```

Or multiline. In this case the first line should be a short summary in one line. Then leave a line empty, and then you can detail the goal of the function, how it works, what are its side effects, etc.

```
9 def square_v2(num):  
10     """Return the square of a given number.  
11  
12     Calculate the square of the input number."""  
13     return num * num
```

(see also: annex F)

Document your programs! Get used to it!

optional parameters / default parameter values

```
>>> def greet(name, greetings="Hello"):
...     print("{g}, {n}!".format(g=greetings, n=name))
...
>>> greet("Laszlo")
Hello, Laszlo!
>>>
>>> greet("Laszlo", greetings="Hola")
Hola, Laszlo!
>>>
>>> greet("Laszlo", "Bonjour")
Bonjour, Laszlo!
```



optional parameters (another example)

```
4 def hello(name, repeat=1, postfix=''):
5     for i in range(repeat):
6         print(name + postfix)
7
8
9 def main():
10    hello('Laci')
11    print('#' * 10)
12    hello('Laci', repeat=3)
13    print('#' * 10)
14    hello('Laci', postfix='!')
15    print('#' * 10)
16    hello('Laci', repeat=3, postfix='!')
17    print('#' * 10)
18    print('#' * 10)
19    hello('Laci', 3)
20    print('#' * 10)
21    hello('Laci', 3, '')
22    print('#' * 10)
23    hello('Laci', '') # error
```



homework

Exercises

1. [[20120818a](#)] distance between two points (tuple)
2. [[20120818d](#)] list comprehensions (to complete)
3. [[20120818e](#)] multiples of 3 or 5 (PE #1)
(this time with list comprehensions)
4. [[20120920e](#)] line break
5. [[20130211b](#)] diamond
6. [[20120818f](#)] sum square difference (PE #6)
7. [[20130305a](#)] XOR (Warning! Requires thinking!)